

چیلر تراکمی آب خنک تک کمپرسور اسکرو مارک Bitzer آلمان به ظرفیت 125 تن تبرید

Condenser water leaving Temp.*F	EWLT.*F	Actual Cap [TON]	Electric		Chilled water		Cooling water	
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	Flow rate [GPM]	Pressure drop [ft]
85	42	103.3	73.4	133.7	274.9	12.4	298.0	5.8
	44	107.3	74.3	134.9	257.4	13.3	308.1	6.2
	45	109.2	74.7	135.6	262.2	13.8	313.2	6.4
	46	111.5	75.1	136.3	267.7	14.4	318.9	6.6
90	42	100.1	77.1	139.4	240.3	11.6	293.0	5.6
	44	104.1	77.9	140.5	249.9	12.6	303.1	6.0
	45	106.1	78.3	141.2	254.7	13.0	308.1	6.2
	46	108.1	78.7	141.8	259.5	13.5	313.2	6.4
95	42	97.0	81.2	145.5	232.8	10.9	288.3	5.4
	44	100.7	81.9	146.6	241.7	11.7	297.6	5.8
	45	102.7	82.3	147.3	246.5	12.2	302.7	6.0
	46	104.7	82.7	147.8	251.3	12.7	307.7	6.2
100	42	93.6	85.4	152.1	224.6	10.1	283.0	5.2
	44	97.3	86.1	153.3	233.5	11.0	292.3	5.6
	45	99.3	86.5	153.8	238.3	11.4	297.4	5.7
	46	101.3	86.9	154.3	243.1	11.9	302.4	5.9
105	42	89.9	90.0	159.2	215.8	9.4	277.2	5.0
	44	93.9	90.6	160.2	225.3	10.2	287.2	5.4
	45	95.6	91.0	160.7	229.4	10.6	291.6	5.5
	46	97.6	91.3	161.3	234.2	11.0	296.5	5.7