

چیلر تراکمی هوا خنک دو کمپرسور اسکرال به ظرفیت 20 تن تبرید

Condensing Temp.*F	*F EWLT	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	16.4	15.3	29.5	39.4	4.5	231.1
	44	17.0	15.3	29.5	40.9	4.8	238.4
	45	17.3	15.3	29.5	41.05	4.9	242.2
	46	17.7	15.3	29.5	42.4	5.1	246.0
120	42	16.0	16.3	30.5	38.4	4.2	228.6
	44	16.6	16.3	30.5	39.8	4.5	235.8
	45	16.8	16.3	30.5	40.4	4.7	239.4
	46	17.2	16.2	30.5	41.2	4.9	243.1
125	42	15.5	17.2	31.7	37.3	4.0	226.2
	44	16.1	17.2	31.7	38.6	4.3	233.1
	45	16.3	17.2	31.7	39.2	4.4	236.6
	46	16.7	17.2	31.7	40.0	4.6	240.2
130	42	15.1	18.3	32.9	36.1	3.7	223.8
	44	15.6	18.2	32.9	37.5	4.0	230.5
	45	15.8	18.2	32.9	38.0	4.1	233.9
	46	16.2	18.2	32.9	38.9	4.3	237.4
140	42	14.1	20.4	35.7	33.9	3.3	219.2
	44	14.6	20.4	35.7	35.1	3.5	225.5
	45	14.8	20.4	35.7	35.6	3.6	228.7
	46	15.1	20.4	35.7	36.3	3.6	231.9