

چیلر تراکمی آب خنک تک کمپرسور اسکرو مارک Bitzer آلمان به ظرفیت 70 تن تبرید

Condenser water leaving Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Cooling water	
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	Flow rate [GPM]	Pressure drop [ft]
85	42	55.2	40.1	74.0	132.5	9.7	159.8	6.7
	44	57.5	40.6	74.7	137.9	10.5	165.6	7.2
	45	58.6	40.8	74.9	140.7	11.0	168.5	7.4
	46	59.7	41.0	75.3	143.4	11.4	171.4	7.7
90	42	53.4	42.0	76.8	128.2	9.1	156.9	6.4
	44	55.6	42.4	77.2	133.6	9.9	162.5	6.9
	45	56.8	42.6	77.6	136.2	10.3	165.3	7.2
	46	58.0	42.8	78.0	139.3	10.7	168.5	7.4
95	42	51.6	44.0	79.7	123.7	8.5	153.8	6.2
	44	53.7	44.4	80.2	129.0	9.2	159.3	6.6
	45	54.8	44.6	80.6	131.6	9.6	162.0	6.9
	46	56.0	44.8	80.9	134.3	10.0	164.9	7.1
100	42	49.6	46.2	83.0	119.0	7.8	150.6	5.9
	44	51.7	46.6	83.4	124.1	8.5	156.0	6.4
	45	52.8	46.8	83.8	126.7	8.9	158.7	6.6
	46	53.9	47.0	84.1	129.4	9.3	161.5	6.8
105	42	47.5	48.6	86.4	114.0	7.2	147.2	5.7
	44	49.6	48.9	87.0	119.0	7.8	152.4	6.1
	45	50.6	49.1	87.3	121.5	8.2	155.1	6.3
	46	51.7	48.3	87.5	124.1	8.5	157.8	