

چیلر تراکمی آب خنک 4 کمپرسور اسکرال به ظرفیت 100 تن تبرید

Condenser water leaving Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Cooling water	
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	Flow rate [GPM]	Pressure drop [ft]
85	42	80.0	56.0	99.8	192.0	12.2	221.2	4.3
	44	83.2	56.4	100.3	199.7	13.2	228.9	4.6
	45	84.9	56.5	100.6	203.7	13.7	232.9	4.7
	46	86.6	56.7	100.8	207.7	14.2	236.9	4.9
90	42	78.1	59.2	104.4	187.4	11.6	218.7	4.2
	44	81.2	59.4	104.9	195.0	12.6	226.1	4.5
	45	82.9	59.6	105.1	198.8	13.1	230.0	4.6
	46	84.5	59.8	105.4	202.8	13.6	233.9	4.8
95	42	76.2	62.5	109.6	183.0	11.1	216.3	4.1
	44	79.3	62.8	109.9	190.3	12.0	223.5	4.4
	45	80.9	62.9	110.2	194.1	12.4	227.2	4.5
	46	82.5	63.1	110.4	197.9	12.9	231.0	4.7
100	42	74.4	66.2	115.1	178.5	10.5	214.1	4.0
	44	77.4	66.4	115.5	185.7	11.4	221.1	4.3
	45	78.9	66.5	115.7	189.3	11.8	224.8	4.4
	46	80.4	66.6	115.9	193.1	12.3	228.4	4.6
105	42	72.5	70.1	121.3	174.0	10.0	212.1	3.9
	44	75.4	70.2	121.6	181.0	10.8	218.9	4.2
	45	76.9	70.4	121.8	184.5	11.2	222.4	4.3
	46	78.4	70.4	121.9	188.2	11.7	226.0	4.5