

چیلر تراکمی هوا خنک دو کمپرسور اسکرال به ظرفیت 30 تن تبرید

Condensing Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	24.7	22.7	41.6	59.2	10.1	346.1
	44	25.6	22.7	41.6	61.4	10.9	357.0
	45	26.0	22.7	41.6	62.3	11.2	362.6
	46	26.5	22.7	41.6	63.5	11.7	368.2
120	42	24.1	24.1	43.4	57.8	9.6	343.1
	44	24.9	24.1	43.4	59.8	10.3	353.7
	45	25.3	24.1	43.4	60.8	10.7	359.1
	46	25.8	24.1	43.4	62.0	11.1	364.6
125	42	23.4	25.6	45.3	56.2	9.1	340.1
	44	24.3	25.6	45.3	58.3	9.8	350.4
	45	24.6	25.6	45.3	59.1	10.1	355.7
	46	25.1	25.6	45.3	60.3	10.5	361.0
130	42	22.8	27.2	47.3	54.7	8.6	337.0
	44	23.6	27.2	47.3	56.6	9.3	347.1
	45	23.9	27.2	47.3	57.5	9.5	352.2
	46	24.4	27.2	47.3	58.6	9.9	357.4
140	42	21.4	30.5	51.8	51.3	7.6	330.7
	44	22.1	30.6	51.8	53.1	8.2	340.2
	45	22.5	30.6	51.8	53.9	8.4	345.0
	46	22.9	30.6	51.8	55.0	8.7	