

مینی چیلر تراکمی هوا خنک تک کمپرسور اسکرال به ظرفیت 5 تن تبرید

Condensing Temp.*F	EWLT.*F	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	3.9	3.7	7.4	9.4	1.3	55.0
	44	4.1	3.7	7.4	9.7	1.4	56.9
	45	4.1	3.7	7.4	9.9	1.5	57.9
	46	4.2	3.7	7.4	10.1	1.5	58.8
120	42	3.8	3.9	7.6	9.1	1.2	54.3
	44	3.9	3.9	7.6	9.4	1.3	56.1
	45	4.0	3.9	7.6	9.6	1.4	57.1
	46	4.1	3.9	7.6	9.8	1.4	58.0
125	42	3.7	4.1	7.9	8.8	1.2	53.6
	44	3.8	4.1	7.9	9.2	1.3	55.4
	45	3.9	4.1	7.9	9.3	1.3	56.3
	46	4.0	4.2	7.9	9.5	1.4	57.2
130	42	3.6	4.4	8.2	8.5	1.1	53.0
	44	3.7	4.4	8.2	8.9	1.2	54.7
	45	3.7	4.4	8.2	9.0	1.2	55.6
	46	3.8	4.4	8.2	9.2	1.3	56.5
140	42	3.3	4.89	8.9	8.0	1.0	52.2
	44	3.5	4.9	8.9	8.3	1.0	53.8
	45	3.5	4.9	8.9	8.5	1.1	54.6
	46	3.6	5.0	8.9	8.6	1.2	55.4