

چیلر تراکمی آب خنک دو کمپرسور اسکرال به ظرفیت 50 تن تبرید

Condenser water leaving Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Cooling water	
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	Flow rate [GPM]	Pressure drop [ft]
85	42	40.0	28.0	49.9	96.0	15.8	110.6	13.7
	44	41.6	28.2	50.2	99.8	17.1	114.4	14.7
	45	42.4	28.3	50.3	101.8	17.8	116.4	15.2
	46	43.3	28.4	50.4	103.9	18.5	118.4	15.8
90	42	39.1	29.6	52.2	93.7	15.1	109.3	13.4
	44	40.6	29.7	52.4	97.5	16.3	113.1	14.4
	45	41.4	29.8	52.6	99.4	17.0	115.0	14.9
	46	42.2	29.9	52.7	101.4	17.6	116.9	15.4
95	42	38.1	31.3	54.8	91.5	14.4	108.1	13.1
	44	39.6	31.4	55.0	95.2	15.5	111.8	14.0
	45	40.4	31.5	55.1	97.0	16.2	113.6	14.5
	46	41.2	31.5	55.2	98.9	16.8	115.5	15.0
100	42	37.2	33.1	57.6	89.3	13.7	107.1	12.9
	44	38.7	33.2	57.7	92.8	14.8	110.6	13.7
	45	39.4	33.3	57.8	94.7	15.4	112.4	14.2
	46	40.2	33.3	57.9	96.5	16.0	114.2	14.7
105	42	36.2	35.0	60.6	87.0	13.0	106.1	12.6
	44	37.7	35.1	60.8	90.3	14.0	109.5	13.5
	45	38.4	35.2	60.9	92.3	14.6	111.2	13.9
	46	39.2	35.2	61.0	94.1	15.2	113.0	14.3