

چیلر تراکمی هوا خنک تک کمپرسور اسکرو مارک Bitzer آلمان به ظرفیت 70 تن تبرید

Condensing Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	49.0	48.6	86.4	117.7	7.7	754.5
	44	51.1	48.9	86.9	122.6	8.3	780.1
	45	52.1	49.1	87.3	125.2	8.7	793.4
	46	53.2	49.3	87.6	127.7	9.0	806.7
120	42	46.9	51.1	90.2	112.6	7.0	737.4
	44	48.9	51.5	90.7	117.4	7.6	762.7
	45	49.9	51.7	91.1	119.8	7.9	775.7
	46	51.0	51.9	91.4	122.4	8.3	789.0
125	42	44.7	53.8	94.2	107.2	6.4	719.7
	44	46.6	54.2	94.7	111.9	6.9	744.6
	45	47.6	54.4	95.1	114.3	7.2	757.2
	46	48.6	54.6	95.4	116.8	7.5	770.2
130	42	42.4	56.6	98.3	101.7	5.7	701.9
	44	44.3	57.0	98.9	106.3	6.3	726.2
	45	45.3	57.2	99.3	108.6	6.5	738.4
	46	46.3	57.4	99.6	111.0	6.8	751.1
135	42	40.0	59.4	102.6	96.1	5.1	683.1
	44	41.9	59.9	103.4	100.5	5.6	707.0
	45	42.8	60.1	103.7	102.8	5.9	719.3
	46	43.8	60.3	104.0	105.2	6.1	731.6

0



TAHVIEH NOVIN
Air conditioner Eng. Co.

شرکت مهندسی تهویه نوین ایرانیان