

چیلر تراکمی هوا خنک تک کمپرسور اسکرو مارک Bitzer آلمان به ظرفیت 80 تن تبرید

Condensing Temp.*F	EWLT.*F	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	57.2	57.8	101.9	137.2	12.8	883.5
	44	59.5	58.2	102.6	142.7	13.9	912.2
	45	60.6	58.4	102.9	145.4	14.4	926.6
	46	61.7	58.6	103.3	148.2	15.0	940.9
120	42	54.9	60.8	106.5	131.7	11.8	866.1
	44	57.2	61.2	107.3	137.2	12.8	895.2
	45	58.3	61.5	107.6	140.0	13.3	909.8
	46	59.5	61.7	107.9	142.7	13.9	942.2
125	42	52.6	64.0	111.4	126.3	10.9	849.7
	44	54.8	64.4	112.0	131.4	11.8	877.1
	45	55.9	64.6	112.4	134.1	12.7	891.1
	46	56.9	64.8	112.7	136.6	9.9	904.0
130	42	50.2	67.2	116.2	120.6	10.8	832.3
	44	52.4	67.6	117.1	125.8	11.2	895.6
	45	53.5	67.9	117.4	128.3	11.7	873.3
	46	54.6	68.1	117.8	131.0	9.0	887.3
135	42	47.8	70.4	121.3	114.7	9.8	813.9
	44	49.9	70.9	122.1	119.8	10.2	840.9
	45	51.0	71.2	122.5	122.3	10.6	845.9
	46	52.1	71.5	122.9	125.0		868.9