

چیلر تراکمی هوا خنک تک کمپرسور اسکرو مارک Bitzer آلمان به ظرفیت 90 تن تبرید

Condensing Temp.*F	*F EWLT.	Actual Cap [TON]	Electric		Chilled water		Heat Rejection [MBH]
			Power [KW]	Current [A]	Flow rate [GPM]	Pressure drop [ft]	
115	42	66.0	65.0	117.9	158.4	7.0	1014.0
	44	68.6	65.4	118.4	164.6	7.6	1046.1
	45	69.7	65.6	118.7	167.3	7.8	1060.4
	46	71.1	65.8	119.1	170.7	8.2	1078.1
120	42	63.7	68.7	123.5	152.9	6.6	999.3
	44	66.3	69.0	124.1	159.1	7.1	1030.0
	45	67.4	69.2	124.4	161.8	7.3	1045.4
	46	68.8	69.4	124.6	165.2	7.6	1063.1
125	42	61.5	72.5	129.4	147.5	6.1	984.9
	44	63.7	72.9	130.0	152.9	6.6	1013.6
	45	64.9	73.1	130.3	155.7	6.8	1028.0
	46	66.3	73.3	130.6	159.1	7.1	1045.7
130	42	58.9	76.4	135.6	141.3	5.6	967.5
	44	61.2	76.8	136.3	146.8	6.0	996.2
	45	62.3	77.0	136.6	149.5	6.3	1010.5
	46	63.7	77.3	137.1	152.9	6.6	1028.6
135	42	56.2	80.3	141.9	134.9	5.1	948.4
	44	58.6	80.9	142.8	140.7	5.5	979.5
	45	59.7	81.1	143.3	143.4	5.8	993.8
	46	60.9	81.4	143.7	146.1	6.0	1008.5